

## Specifications

Model		HJ6120G-E12
<b>Dimensions</b>	Overall Length (mm)	4,730
	Overall Width (mm)	2,240
	Overall Height (mm)	2,680
	Weight (kg)	4,785
<b>Engine</b>	Number of cylinder	4
	Displacement (cc)	2,999
	Output (ps/rpm)	120/2,500
	Fuel tank capacity (l)	100
<b>Traveling System &amp; Equipments</b>	Crawler width (mm)	550
	Crawler grounding length (mm)	1,825
	Crawler tread (mm)	1,150
	Ground pressure (kg/cm <sup>2</sup> )	0.236
	Number of speed range	2
	Working speed (m/s)	0-2.00
	Traveling speed (m/s)	0-3.11
<b>Reaping section</b>	Reaping row	6
	Reaping width (mm)	1,950-2,025
	Cutter bar width (mm)	1,990
	Applicable crop length (mm)	550-1,300
<b>Threshing section</b>	Threshing method	Under feeding axial flow type
	Threshing drum Dia.x width (mm)	446 X 1,250
	Re-threshing drum Dia.x width (mm)	76 X 1,030
	Diffusion drum Dia.x width (mm)	120 X 820
	Grain tank capacity (l)	2000

Note: The technical features may be altered without prior notice.