

		SF235	SF224	
Dimension	Overall length (mm)	3,350(with SCMB60), 3,160(with SCMA54)		
	Overall width (mm)	1,245 1,575 (with SCMB60), 1,445 (with SCMA54)		
	Overall height (mm)	1,776 (with ROPS: 2,120)		
	Wheelbase (mm)	1,275		
	Weight (incl. mower & collector) (kg)	1,270	1,180	
Engine	Model	E3CD	E3112	
	Number of cylinder	3		
	Displacement (L)	1.498	1.123	
	Output (net) (kW{PS})	24.2{32.9}	16.1{21.9}	
	Rated speed (min-1)	2,600		
	Emission regulation	Stage3A	-	
	Fuel tank capacity (L)	40		
Transmission	Transmission	HST		
	HST pedal	2 pedals		
	Auto accelerator	Std		
PTO	Front side (for mower)	Clutch Rate speed (min-1)	Wet disk (Independent) 1,988 @2,600	
	Front center (for blower)	Clutch	Std Wet disk (Independent)	
Front axle	Diff. lock	Std (Lh)		
	Brake	Type	Dry dram	
		Position	Lh	
	Parking brake	Lever		
	Max. traveling speed	Forward (km/h)	15	
Reverse (km/h)		10		
Tire	Turf	Front	23x10.50-12	
		Rear	18x8.5-8	
Rear axle	4WD/2WD	Auto or 4WD		
	Steering	Power steering		
	Tilt steering	Std		
	Aux. valve for mower deck & collector	Std (3 valves)		
Electric	Front light & rear combination lamp		Std (homologated)	
	Meter	Fuel gauge	Std (Electric)	
		Hour meter	Std	
	Warning lamp	Battery charge		Std
		Engine oil pressure		Std
		Engine water temperature		Std (with buzzer)
		Parking brake		Std
		Collector full		Std (with buzzer)
4WD-On		Std		
Exterior	Engine hood		Tilt	
	Seat		Factory opt (Z model: armrest & suspension seat)	
	Floor mat		Std	
	Rear weight		Opt (without blower model is std.)	
ROPS		Std (foldable)		

		SCMB60	SCMA54	SSM54
Mower	Cutting width (inch)	60"	54"	54"
	Discharge	Center	Center	Side
	Number of blade	2	2	3
	Flip-up angle	65°	65°	60°
	Cutting height adjustment	1 action lever	1 action lever	Pin type
	Min. cutting height (mm)	25	25	30

		SBC950
Collector	Capacity (L)	950
	Container	Plastic
	Dump	Hydraulic
	Lift	Hydraulic
	Dump height (mm)	2,125