

		TM3267F	TM3247F	TM3217F	
Dimension	Overall length (mm)	2,880 (with 3-point linkage)	2,815 (with 3-point linkage)		
	Overall width (mm)	1,110/1,245			
	Overall height (with ROPS) (mm)	2,420 (with rear ROPS) 2,040 (with center ROPS)	2,390 (with rear ROPS) 2,010 (with Center ROPS)		
	Wheelbase (mm)	1,560			
	Weight (with Agri Tire) (kg)	875	855		
Engine	Manufacturer	ISEKI			
	Model	E3CD	E3112		
	Number of Cylinder	3			
	Displacement (L)	1.498	1.123		
	Output	Gross kW (HP)	18.9 (25.3)	16.8 (22.5)	14.5 (19.4)
		Net kW (HP)	18.7 (25.1)	16.1 (21.6)	14.3 (19.2)
	Rated engine rotation (min-1)	2,600		2,500	
Fuel tank capacity (L)	28				
Transmission	Main clutch	Dry single			
	Shuttle	Synchro			
	Main	4			
	Sub	2			
	Number of speed	F8/R8			
PTO	Clutch	One way clutch			
	Mid PTO	Factory Opt.			
	Rear PTO Stage	1			
Rear Axle	Diff. lock	Std. (Right pedal)			
	Brake	Wet disk			
	Brake pedal	2 Pedals (Right)			
	Parking brake	Lever			
	Max. speed	Forward (km/h)	22.2*	20.1*	
Reverse (km/h)		19.7*	17.9*		
Tire	Agri	Front	6.00-12	06月12日	
		Rear	9.5-18	9.5-16	
	Turf	Front	24x8.50-12	22x8.50-12	
		Rear	315/75D-15	31x13.5-15	
Front Axle	4WD/2WD	2WD,4WD			
Hydraulic	Steering	Power steering			
	3-point linkage lift capacity	at link end (kgf)	600 (opt:800)	600	
		at 24" behind (kgf)	450		
	Main (L/min)	20.8		20.1	
	Sub (L/min)	12.2		11.9	
	Position control	Std.			
	Aux. valve	2 valves (max. x2)	1 valve (max. x2)		
3-point Linkage	3-point linkage category	Category1			
Electric	Rear hitch	Clevis drawbar			
	Head right	Std.			
Exterior	Beacon lamp switch	Std.			
	Rear-view mirror	Std. (RH&LH)			
ROPS	Seat	Factory OPT. (Z model std.) Rear ROPS(R model), Center ROPS (A model)			

*With Agri tire (TY3245F1E)

		TM3267H	TM3247H	TM3217H	
Dimension	Overall length (mm)	2,880 (with 3-point linkage)	2815 (with 3-point linkage)		
	Overall width (mm)	1,110/1,245			
	Overall height (mm)	2,420 (with rear ROPS) 2,040 (with Center ROPS)	2,390 (with rear ROPS) 2,010 (with Center ROPS)		
	Wheelbase (mm)	1,560			
	Weight (kg)	875	855		
Engine	Manufacturer	ISEKI			
	Model	E3CD	E3112		
	No. of Cylinder	3			
	Displacement (L)	1.498	1.123		
	Output	Gross kW (HP)	18.9 (25.3)	16.8 (22.5)	14.5 (19.4)
		Net kW (HP)	18.7 (25.1)	16.1 (21.6)	14.3 (19.2)
	Rated engine rotation (min-)	2,600		2,500	
	Fuel tank capacity (L)	28			
Transmission	Main	HST			
	Sub	3			
	Number of speed	F3/R3			
	HST	Pedal	2 Pedals		
		Auto accelerator	Std.		
Auto cruise		Mechanical			
PTO	Clutch	Independent			
	MID PTO	Std.			
	Rear PTO	1			
	Rotation speed (min-1)	571	550		
Rear axle	Diff. lock	Std.(Left Pedal)			
	Brake	Wet disk			
	Brake pedal	1 Pedal (Right)			
	Parking brake	Lever			
	Max. speed	Forward (km/h)	22.4*	19.4*	
		Reverse (km/h)	15.3*	14.5*	
Tire	Agri	Front	6.00-12		
		Rear	9.5-18		
	Turf	Front	24x8.50-12		
		Rear	315/75D-15		
			22x8.50-12		
Front axle	2WD/4WD	2WD,4WD			
	Steering	Power steering			
Hydraulic	3-point linkage lift capacity	@ link end (kgf)	600 (opt:800)	600	
		@ 24 behind (kgf)	450		
	Main (L/min)	20.9		20.1	
	Power steering (L/min)	12.3		11.9	
	Position control	Std.			
	Aux. Valve	2 valves (max. x2)			
3-point linkage	3-point linkage category	Category 1			
	Rear hitch	Clevis drawbar			
	Beacon lamp switch	Std.			
Exterior	Rear-view mirror	Std. (R&L)			
	Seat	Factory OPT. (Z model std.)			
ROPS	Rear ROPS (Foldable)				

*With Agri tire (TY3245F1E)